RIMAGE SIMPLEX™ USB AUTOMATION

Simplicity Meets Reliability in USB Publishing

Simplex: The next evolution in automated USB production, shaped by customer feedback to deliver the results that modern workflows require. Engineered for robust performance with lightweight, industrial-grade robotics, Simplex meets the world's most challenging digital content demands for USB technology. Advanced features such as flexible memory options combined with our software suite bring you unrivaled performance and quality.



Precision printing

Simplex delivers clean, professional printing with ease. Crisp, consistent output ensures clear branding and text readability, perfect for upholding brand integrity at scale.



Simply automated

Designed to accelerate your entire workflow: Streamlined robotics and software reduce manual touchpoints and lower operational costs, while delivering the flexibility to produce hundreds of customized USBs per day.

Powerful performance

Built for the long haul, Simplex combines modular flexibility with lasting durability. Configure up to four different data recorders with 120-unit input and output capacity standard, backed by robotics engineered for years of reliable, continuous production.

Features

- USB 3.1 Gen 1 data modules from 8GB to 128GB capacity
- 120-unit input/ouput capacity
- Four data recorders that work simultaneously
- Access finished media without interrupting workflows
- 360 degree visible status light
- Multi-line LCD status display
- Rapid start-up with high throughput capability

Intelligent Design

A fraction of the size of previous models, Simplex delivers a lighter footprint without sacrificing capability. The accessible top cover design ensures easy hardware maintenance and serviceability.

SYSTEM SPECIFICATIONS

	SIMPLEX
Input Capacity	120 USBs
Output Bin Capacity	120 USBs
Printer	Prism III/CP
Rimage Simplex Software Suite (RSSS)	A full set of software tools enabling unique artwork design, job submission, control center operation, production monitoring and custom application creation.
Rimage Quick Design™	Label creation software – included
Height	15.4 in / 39 cm
Width	15.7 in / 40 cm
Depth*	23.6 in / 60 cm
Height w/ Cover Lifted	29.1 in / 74 cm
Weight w/ Prism III / CP	42.2 lb / 19.2 kg
Power Specifications	100-240 VAC, 60/50 Hz
Power Consumption	~10W idling / ~50W operating
Warranty	12 months

We Recommend

Rimage Maintenance Agreements

Maximize your ROI and minimize downtime when quick problem resolution is a must. With our range of skilled technicians and industry-leading support services, Rimage has a maintenance plan that meets your needs.

Rimage Media

Get reliable, uninterrupted performance from your Simplex. With optimized print ribbons and Simplex USB modules, you'll get the best-looking, longest-lasting results.

For complete information about Rimage Simplex Series support options, visit www.rimage.com.



